

Manufacturer/distributor: PyraSied Xtreme Acrylic

Brand: Versato®

Material: Clear Acrylic tubes

Tolerance¹

Cast acrylic tubes

External ø mm	Wall Thickness mm	Tolerance External ø	Tolerance Thickness 3-10 mm	Tolerance Thickness 12-15 mm
40	3;4	+1%,-0,5%	± 1mm	/
44	3;4;5	+1%,-0,5%	± 1mm	/
50	3;4;5;6	+1%,-0,5%	± 1mm	/
60	3;4;5;6;7;8;10	+1%,-0,5%	± 1mm	/
64	3;4;5;6;7;8;10	+1%,-0,5%	± 1mm	/
70	3;4;5;6;7;8;10;12-15	+1%,-0,5%	± 1mm	± 1,5mm
76	3;4;5;6;7;8;10;12-15	+1%,-0,5%	± 1mm	± 1,5mm
80	3;4;5;6;7;8;10;12-15	+1%,-0,5%	± 1mm	± 1,5mm
90	3;4;5;6;7;8;10;12-15	+1%,-0,5%	± 1mm	± 1,5mm
100	3;4;5;6;7;8;10;12-15	+1%,-0,5%	± 1mm	± 1,5mm
102	3;4;5;6;7;8;10	+1%,-0,5%	± 1mm	/
110	3;4;5;6;7;8;10;12-15	± 0,5%	± 1mm	± 1,5mm
115	3;4;5;6;7;8;10;12-15	± 0,5%	± 1mm	± 1,5mm
120	3;4;5;6;7;8;10;12-15	± 0,5%	± 1mm	± 1,5mm
125	3;4;5;6;7;8;10;12-15	± 0,5%	± 1mm	± 1,5mm
127	3;4;5;6;7;8;10	± 0,5%	± 1mm	/
134	3;4;5;6;7;8;10;12-15	± 0,5%	± 1mm	± 1,5mm
139	3;4;5;6;7;8;10;12-15	± 0,5%	± 1mm	± 1,5mm
150	3;4;5;6;7;8;10;12-15	± 0,5%	± 1mm	± 1,5mm
153	3;4;5;6;8;10	± 0,5%	± 1mm	/
160	3;4;5;6;7;8;10;12-15	± 0,5%	± 1mm	± 1,5mm
164	3;4;5;6;7;8;10;12-15	± 0,5%	± 1mm	± 1,5mm
170	3;4;5;6;7;8;10;12-15	± 0,5%	± 1mm	± 1,5mm
185	3;4;5;6;7;8;10;12-15	± 0,3%	± 1mm	± 1,5mm
200	3;4;5;6;7;8;10;12-15	± 0,3%	± 1mm	± 1,5mm
215	3;4;5;6;7;8;10	± 0,5%	± 1mm	/

¹ Tolerances on roundness, straightness and optical performances: please ask our sales & support department.

This information is given as a guide and does not represent the technical specifications of the materials and therefore does not imply any responsibility on the part of PyraSied B.V. It's the responsibility of each user to establish that the material is suitable for his or her application.

PYRASIED XTREME ACRYLIC®

☎ +31(0)58-76 76 100 ✉ sales@pyrasied.nl 🌐 www.pyrasied.nl

External ø mm	Wall Thickness mm	Tolerance External ø	Tolerance Thickness 3-10 mm	Tolerance Thickness 12-15 mm
220	3;4;5;6;7;8;10;12-15	± 0,3%	± 1mm	± 1,5mm
230	3;4;5;6;7;8;10;12-15	± 0,3%	± 1mm	± 1,5mm
240	3;4;5;6;7;8;10;12-15	± 0,3%	± 1mm	± 1,5mm
250	3;4;5;6;7;8;10;12-15	± 0,3%	± 1mm	± 1,5mm
260	3;4;5;6;7;8;10;12-15	± 0,3%	± 1mm	± 1,5mm
270	3;4;5;6;8;10;12-15	± 0,3%	± 1mm	± 1,5mm
300	3;4;5;6;7;8;10;12-15	± 0,3%	± 1mm	± 1,5mm
350	4;5;6;7;8;10;12-15	± 0,3%	± 1mm	± 1,5mm
400	4;5;6;7;8;10;12-15	± 0,3%	± 1mm	± 1,5mm
450	4;5;6;8;10;12-15	± 0,3%	± 1mm	± 1,5mm
500	5;6;7;8;10; 12-15	± 0,3%	± 1mm	± 1,5mm
550	5;6;8;10	± 0,3%	± 1mm	/
610	5;6;8;10;12-15	± 0,3%	± 1mm	± 1,5 mm

Extruded acrylic tubes

External ø mm	Wall Thickness mm	Tolerance External ø	Tolerance Thickness mm
5	1	± 0,3mm	±0,20
7	1	± 0,3mm	±0,20
8	2	± 0,3mm	±0,20
10	1,5/2/3	± 0,3mm	± 0,20/0,25/0,30
12	1/2/3	± 0,3mm	± 0,20/0,25/0,30
13	1,5/2/3	± 0,3mm	± 0,20/0,25/0,30
15	1/2/2,5/3	± 0,3mm	± 0,20/0,25/0,30/0,35
16	2	± 0,3mm	±0,25
18	2/3	± 0,3mm	± 0,25/0,30
20	1/2/3	± 0,3mm	± 0,20/0,25/0,30
22	2/3	± 0,3mm	± 0,25/0,30
24	2/3	± 0,5mm	± 0,25/0,30
25	2/3	± 0,5mm	± 0,25/0,30

This information is given as a guide and does not represent the technical specifications of the materials and therefore does not imply any responsibility on the part of PyraSied B.V. It's the responsibility of each user to establish that the material is suitable for his or her application.

PYRASIED XTREME ACRYLIC®

☎ +31(0)58-76 76 100 ✉ sales@pyrasied.nl 🌐 www.pyrasied.nl

External ø mm	Wall Thickness mm	Tolerance External ø	Tolerance Thickness mm
26	2/3	± 0,5mm	± 0,25/0,30
28	2/3	± 0,5mm	± 0,25/0,30
30	2/3/4/5	± 0,5mm	± 0,25/0,30/0,35/0,40
32	2/3/4/5	± 0,5mm	± 0,25/0,30/0,35/0,40
34	2/3/4/5	± 0,5mm	± 0,25/0,30/0,35/0,40
36	2/3/4/5	± 0,5mm	± 0,25/0,30/0,35/0,40
38	3	± 0,5mm	±0,30
40	2/3/4/5	± 0,8mm	± 0,25/0,30/0,35/0,40
44	2/3/4/5	± 0,8mm	± 0,25/0,30/0,35/0,40
45	2/3	± 0,8mm	± 0,25/0,30
50	2/3/4/5	± 0,8mm	± 0,25/0,30/0,35/0,40
56	2/3/4/5	± 0,8mm	± 0,25/0,30/0,35/0,40
60	2/3/4/5	± 0,8mm	± 0,25/0,35/0,35/0,40
64	2/3/4/5	± 0,8mm	± 0,25/0,35/0,35/0,40
70	2/3/4/5	± 0,8mm	± 0,30/0,35/0,40/0,45
76	3/4/5	± 0,9mm	± 0,35/0,40/0,45
80	2/3/4/5	± 0,9mm	± 0,30/0,35/0,40/0,45
90	3/4/5	± 0,9mm	± 0,35/0,40/0,45
100	2/3/4/5	± 1,2mm	± 0,30/0,35/0,40/0,45
110	3/4/5	± 1,2mm	± 0,35/0,40/0,45
120	2/3/4/5	± 1,2mm	± 0,30/0,35/0,40/0,45
125	3/4/5	± 1,3mm	± 0,35/0,45
130	3/4/5	± 1,3mm	± 0,35/0,40/0,50
133	3/5	± 1,3mm	± 0,35/0,50
134	3/4/5	± 1,3mm	± 0,35/0,40/0,50
150	3/4/5	± 1,5mm	± 0,40/0,45/0,50
160	3/4/5	± 1,5mm	± 0,40/0,45/0,50
170	3/4/5	± 1,5mm	± 0,40/0,45/0,50
180	3/4/5	± 1,5mm	± 0,40/0,50/0,55
200	3/4/5	± 2,0mm	± 0,40/0,50/0,55
220	3	± 2,0mm	±0,40
230	4/5	± 2,0mm	± 0,50/0,55
250	3/4/5	± 2,0mm	± 0,40/0,50/0,55

Standard tubes are clear. Packing unit: wrapped in PE film. Standard package: included in the price. On request: other lengths, material, colours. If not on stock, MOQ for standard item is: Until OD 38mm = 100 tubes. From OD 40mm = 50 tubes.

This information is given as a guide and does not represent the technical specifications of the materials and therefore does not imply any responsibility on the part of PyraSied B.V. It's the responsibility of each user to establish that the material is suitable for his or her application.

Extruded acrylic tubes satin & opal

External ø mm	Wall Thickness mm	Tolerance External ø	Tolerance Thickness
60	3	± 0,8 mm	± 0,35 mm
70	3	± 0,8 mm	± 0,35 mm
80	3	± 0,9 mm	± 0,35 mm
90	3	± 0,9 mm	± 0,35 mm
100	3	± 1,2 mm	± 0,35 mm
120	3	± 1,2 mm	± 0,35 mm
150	3	± 1,5 mm	± 0,40 mm
160	3	± 1,5 mm	± 0,40 mm
200	3	± 1,5 mm	± 0,40 mm
250	3	± 1,5 mm	± 0,40 mm

This information is given as a guide and does not represent the technical specifications of the materials and therefore does not imply any responsibility on the part of PyraSied B.V. It's the responsibility of each user to establish that the material is suitable for his or her application.

PYRASIED XTREME ACRYLIC®

☎ +31(0)58-76 76 100 ✉ sales@pyrasied.nl 🌐 www.pyrasied.nl